

(19)

Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 1 219 756 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:

03.07.2002 Bulletin 2002/27

(51) Int Cl.7: E04C 3/07, E04C 2/32,
A47B 96/14, A47B 96/20

(21) Application number: 01129403.0

(22) Date of filing: 10.12.2001

(84) Designated Contracting States:

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR

Designated Extension States:

AL LT LV MK RO SI

(30) Priority: 29.12.2000 IT MI002880

(71) Applicant: Briosi, Antonello

20123 Milano (IT)

(72) Inventor: Briosi, Antonello

20123 Milano (IT)

(74) Representative: Lecce, Giovanni

Dott. Giovanni Lecce & C. S.r.l.


Via G. Negri 10

20123 Milano (IT)

(54) Component for load-bearing structures, particularly useful for shelves

(57) A component for load-bearing structures (10), particularly suitable for shelves, obtained from metal by bending a sheet (12), and provided, along its lateral surface, with at least a corrugated or sinusoidal zone, formed by the alternation of recesses (14) and protrusions (16) with a substantially circular profile. Said recesses (14) and protrusions (16) have a thickness equivalent to that of said sheet in its rectilinear parts, and are connected by zones (20) having a lower thickness with respect to that of said sheet.

sions (16) with a substantially circular profile. Said recesses (14) and protrusions (16) have a thickness equivalent to that of said sheet in its rectilinear parts, and are connected by zones (20) having a lower thickness with respect to that of said sheet.



Description

[0001] The present invention relates to a component for load-bearing structures, particularly useful for shelves.

[0002] More particularly, the present invention relates to an element or component for load-bearing structures, especially intended for being utilized for the realization of industrial shelves from metal, forming the warehouses of finished products, raw materials, unfinished products and goods in general.

[0003] As is known, the storage of products involves the preparation of specific equipped areas in the inside of building facilities; said areas are sometime fitted out in the inside of, or near to, production factories, or they constitute installations displaced to distribution or handling points for said products. Said areas intended for containing goods are traditionally formed by metal shelves that develop vertically from the floor or the ground surface of facilities intended for storing. Often, they are articulated along several parallel lines, defining passage corridors for automatically controlled means that put in or take out from the different spaces said products that in some cases may be pelletized. The trend that has been followed for a long time is that of vertically developing the structures to be used as warehouses; as a consequence, the shelves utilized are so sized as to be able to support very high loads.

[0004] This requirements concern especially the uprights, i.e. the vertical load-bearing components which are exposed to the highest stresses, especially if shelves are vertically developed for many meters.

[0005] The uprights of the shelves are, in fact, the components that are subject to the highest strains, as all the tensions and weights that burden the superposed shelves of the structure are transferred on them. Theoretically, the load strains that burden the lower part of the uprights are higher than the overlying ones, so that it would be desirable to realize said uprights according to a differentiated structure, i.e., a structure having a resistance and a loading capacity higher at the basis and progressively reduced upwards. However, a solution of this type involves remarkable construction difficulties, mainly due to the box-like shape of the uprights. Besides, such solution causes high wastes of material, with an ensuing increase in the overall production costs.

[0006] In order to overcome these problems, there have been designed components for load-bearing structures - uprights and the like - provided with stiffening ribs obtained during the molding or bending steps of said components. However, also this solution, while being effective, requires a high amount of material to realize the shapes. The development of the basic sheet is, in other words, markedly more extended with respect to the one conventionally used.

[0007] Object of this invention is to obviate the aforesaid drawbacks.

[0008] More particularly, object of this invention is to

realize a component for load-bearing structures, particularly suitable for shelves, having characteristics of high resistance against stresses and loads, without involving construction difficulties for its realization.

5 [0009] A further object of the invention is to provide a component for load-bearing structures as defined above and suitable to present, if necessary, characteristics of high resistance along prefixed zones of its development, at a constant or a differentiated level.

10 [0010] A further object of the invention is to realize a high resistance component for load-bearing structures that does not originate wastes during the production, and such as not to require, as a starting base, a sheet having a higher development with respect to those used traditionally.

15 [0011] A further object of the invention is to provide users with a component for load-bearing structures suitable to ensure a high level of reliability in the time, and also such as to be easily and economically realizable.

20 [0012] These and still other objects, which will be more apparent thanks to the following description, are achieved by the component for load-bearing structures of the present invention, particularly useful for the realization of shelves, obtained from metal by bending a sheet and provided along its lateral surface with at least a corrugated or sinusoidal zone, formed by the alternation of recesses and protrusions with a substantially circular profile, having a thickness equivalent to that of said sheet in its rectilinear parts, connected by zones (20) having a lower thickness with respect to that of said sheet.

30 [0013] The constructive and functional characteristics of the component for load-bearing structures of the present invention will be better understood thanks to the following description, wherein reference is made to the attached drawings that represent a preferred non limiting embodiment, and wherein:

40 Figure 1 shows a schematic top view of the sheet for the realization of the component for load-bearing structures of the present invention;

45 Figure 2 shows a schematic cross-section of said component for load-bearing structures of Figure 2; Figure 3 shows a schematic partial and magnified cross-section of the same component for load-bearing structures of the preceding figures;

50 Figures 4 and 5 show schematic views of a cross-section of as many alternatives of the component for load-bearing structures of the present invention; Figure 6 shows a schematic portion of the equipment for the realization of the component for load-bearing structures of the present invention.

55 [0014] With reference to the aforesaid figures, the component for load-bearing structures of the present invention, indicated as a whole by 10 in Figure 2, is constituted of a metal structural bar having a substantially quadrangular section, for instance an upright for

shelves.

[0015] Said structural bar, of any length, is obtained by bending a sheet 12 previously cut to measure, to form a body of a box-like shape that is closed and stabilized along its free edges connected by welding stitches.

[0016] According to the invention, along one or more faces of the section bar forming the component for load-bearing structures 10 a plurality of recesses is obtained that have a substantially semicircular profile 14, longitudinally or only partly extended, that gives rise to a sinusoidal or corrugated development of the lateral surface of said section bar. Said recesses 14 are alternated to protrusions 16 having the same substantially semicircular profile, that are cantilevered on the opposite fronts of sheet 12, in its rectilinear parts, according to a direction orthogonal with respect to the longitudinal axis of said sheet. The thickness of said sheet in the zones having a sinusoidal or corrugated development is diversified and results to be greater in correspondence of each of protrusions 16, opposite to a recess 14. The portions having a greater thickness are indicated by 18 in Figure 3, and such thickness approximately corresponds to that of sheet 12 in its rectilinear parts. The connection zones indicated by 20 between each protrusion 16 corresponds to recess 14 have instead a lower thickness with respect to portions 18 and sheet 12 in correspondence of the rectilinear parts.

[0017] The greatest thickness, that concerns each of portions 18, is realized along a direction orthogonal to the longitudinal axis of sheet 12 and with regard to an upright, it concerns therefore only the parts that are more subject to load stresses. Because of the differentiated thickness, a corrugated development of this type does not involve the shortening of the starting sheet 12, as in practice the material is only shifted from one less stressed zone to an adjoining more stressed zone. The connection zones 20 having a lower thickness make up for the amount of necessary material, that would obviously be greater if said zones would have a thickness equal to that of portions 18.

[0018] Recesses 14 and protrusions 16 may have either a constant or a variable pitch; the recesses and protrusions having a constant pitch are preferred.

[0019] Figures 4 and 5 show schematically additional possible configurations of a box-like shaped body suitable to form, for instance, the upright of shelves. In the example of Figure 4, recesses 14 and protrusions 16 that originate portions having a corrugated development concern only partly the opposite box-like shaped body side. In the example of Figure 5 said portions are obtained along the opposite heads defined by the shorter sides of said body. In the example of Figure 5, the box-like shaped body is formed by two complementary half-parts 24, 26, connected with each other by integral flanges 28 with welding stitches or like fastening means.

[0020] Recesses 14 and protrusions 16 are preferably realized by means of a forming machine, known *per se*, provided with couples of rollers like those schematized

by way of example in Figure 6. The rollers suitable to form recesses 14 alternated to protrusions 16 are indicated by 30, 32 in the same figure, and are opposite to each other, with a profile complementary to that of said recesses and protrusions. Sheet 12 is located between said rollers.

[0021] Tests carried out by the applicant have stressed that a component for load-bearing structures provided with one or more corrugated or sinusoidally developed sectors has characteristics of collapse resistance markedly higher with respect to a corresponding traditional component, i.e. a component with a smooth surface.

[0022] As can be inferred from the above description, the advantages that the load-bearing element of the present invention allows to achieve are evident.

[0023] In the component for load-bearing structures of the present invention, the increase in resistance is actual and may be modulated depending on the number, the development and the localization of the corrugated parts obtained along its lateral surface. The creation of said corrugated parts, besides, does not cause a reduction in the development of the body, as the material used is shifted from one to another zone, and the parts subjected to a lower stress that have a reduced thickness made up for the necessary amount of material.

[0024] While the present invention has been described above with reference to some embodiments reported by way of non limitig example, it is evident that modifications and variants will be apparent to those skilled in the art, in the light of the above reported description.

[0025] So, for instance, the solution that has been described above with reference to an upright for shelves may be utilized for other components of said shelves, such as for instance tie-rods or stringers and shelves.

[0026] It is therefore understood that the present invention intends to comprise all the modifications and variants that fall within the spirit and the protection scope of the following claims.

Claims

1. A component for load-bearing structures (10), particularly suitable for shelves, obtained from a metal sheet (12), **characterized in that** said component (10) is provided, along its lateral surface, with at least a corrugated or sinusoidal zones, formed by the alternation of recesses (14) and protrusions (16) with a substantially circular profile; said recesses (14) and profiles (14) having a thickness substantially equivalent to that of the sheet in its rectilinear parts, and being connected by zones (20) having a lower thickness with respect to that of said sheet.
2. The component for load-bearing structures according to claim 1, **characterized in that** said protru-

sions (16) are cantilevered on the opposite fronts of sheet (12) according to a direction orthogonal to the longitudinal axis of said sheet.

3. The component for load-bearing structures according to claims 1 or 2, **characterized in that** said recesses (14) and protrusions (16) have a constant pitch. 5
4. The component for load-bearing structures according to the preceding claims, **characterized in that** it is constituted by a box-like shaped body having a quadrangular section, provided with at least on one of its lateral surfaces with recesses (14) and protrusions (16). 10 15
5. The component for load-bearing structures according to the preceding claims, **characterized in that** said recesses (14) and protrusions (16) are longitudinally extended. 20
6. The component for load-bearing structures according to any of the preceding claims, **characterized in that** recesses (14) and protrusions (16) form portions having a corrugated profile that concern only a part of the opposite sides of the box-like shaped body. 25
7. The component for load-bearing structures according to any of the claims 1-5, **characterized in that** recesses (14) and protrusions (16) form portions having a corrugated development that concern the opposite heads defined by the shorter sides of the box-like shaped body. 30 35
8. The component for load-bearing structures according to claim 7, **characterized in that** the box-like shaped body is formed by two complementary half-parts (24, 26) connected to each other by flanges (28) fastened with each other. 40
9. The component for load-bearing structures according to any of the preceding claims, **characterized in that** recesses (14) and protrusions (16) are obtained by means of a forming machine with shaped rolls (30-32). 45
10. Use of the load-bearing structures according to any of the preceding claims load-bearing structures according to any of the preceding claims for the formation of an upright, a tie-rod and/or a shelf top. 50

55

Fig. 1









Fig. 3







European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 01 12 9403

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	EP 0 279 798 A (PLANNJA AB) 24 August 1988 (1988-08-24)	1-3,10	E04C3/07 E04C2/32 A47B96/14 A47B96/20
Y	* abstract; figure 10 * * column 1, line 28 - line 37 * * column 3, line 51 - column 4, line 15 *	4-6,9	
Y	US 3 165 815 A (ALFRED WOGERBAUER) 19 January 1965 (1965-01-19) * column 4, line 62 - column 5, line 3; figures 8-10,21 *	4-6,9	
A	US 4 969 346 A (BOSL GEORGE F ET AL) 13 November 1990 (1990-11-13) * abstract; figures 1,10 * * column 15, line 25 - line 37 *	1-3,5,9	
A	GB 355 244 B (RICHARDS) 1 April 1941 (1941-04-01) * page 1, line 53 - line 76; figures 1,2 *	1-3	
			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
			E04C A47B
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 26 March 2002	Examiner Jones, C
CATEGORY OF CITED DOCUMENTS		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	
X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document			

EPC FORM 1503 03 92 (P24C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 01 12 9403

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

26-03-2002

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 0279798	A	24-08-1988	SE 459672 B	24-07-1989
			CA 1297255 A1	17-03-1992
			DE 3860797 D1	22-11-1990
			DK 77488 A ,B,	17-08-1988
			EP 0279798 A1	24-08-1988
			FI 880702 A ,B,	17-08-1988
			JP 63255453 A	21-10-1988
			NO 880652 A	17-08-1988
			SE 8700623 A	17-08-1988
			US 4862666 A	05-09-1989
US 3165815	A	19-01-1965	CH 412757 A	15-05-1966
			DE 1452122 A1	12-03-1970
			FI 49684 B	02-06-1975
			GB 989027 A	14-04-1965
US 4969346	A	13-11-1990	US 4770018 A	13-09-1988
			US 4881355 A	21-11-1989
			AT 88529 T	15-05-1993
			AU 594757 B2	15-03-1990
			AU 7129787 A	09-10-1987
			BR 8706208 A	23-02-1988
			CA 1316766 A1	27-04-1993
			DE 3785529 D1	27-05-1993
			DE 3785529 T2	02-12-1993
			EP 0259479 A1	16-03-1988
			GR 870411 A1	09-09-1987
			IL 81758 A	05-11-1990
			KR 9410448 B1	22-10-1994
			MX 169297 B	29-06-1993
			NZ 228615 A	26-07-1990
			WO 8705651 A1	24-09-1987
			CN 87101818 A ,B	20-01-1988
			CN 1050508 A ,B	10-04-1991
			EG 18252 A	30-08-1992
			ES 2004557 A6	16-01-1989
			JP 2853123 B2	03-02-1999
			JP 63502733 T	13-10-1988
			ZA 8701801 A	25-11-1987
GB 355244	B	19-08-1931	NONE	

EPO FORM 8003

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82